


Schockventil

TYPE
VAU



HYDRAULIC DIAGRAM



DUAL CROSS RELIEF VALVES

USE AND OPERATION:

Made up by 2 relief valves with crossed tank, this valve is used to block pressure to a certain setting in the 2 ports of an actuator/hydraulic motor. It's ideal to provide protection against sudden shock pressures and to adjust different pressures in the 2 ports of an hydraulic circuit as well.

MATERIALS AND FEATURES:

Body: zinc-plated steel
Internal parts: hardened and ground steel.
Seals: BUNA N standard
Poppet type: minor leakage

APPLICATIONS:





Connect V1 and V2 to the pressure flow or to the actuator/ hydraulic motor. Vice versa for the remaining ports V1 and V2. Mounting by the actuator is highly recommended in order to avoid pressure drops.

ON REQUEST


- different setting range (see the table)
- other settings available (CODE/T000 please specify the desired setting)

PRESSURE / FLOW

Oil temperature: 50° C - Oil viscosity: 30 cSt



CODE	TYPE	MAX FLOW lt. / min
V0438	VAU 1/4"	30
V0440	VAU 3/8"	45
V0450	VAU 1/2"	70
V0460	VAU 3/4"	110



5

CODE	TYPE	V1 - V2 GAS	L mm	L1 mm	L2 mm	L3 mm	H mm	S mm	WEIGHT Kg
V0438	VAU 1/4"	G 1/4"	60	156	26	54	70	30	0,988
V0440	VAU 3/8"	G 3/8"	80	176	33	54	70	30	1,208
V0450	VAU 1/2"	G 1/2"	80	200	38	54	70	30	1,150
V0460	VAU 3/4"	G 3/4"	95	215	44	54	80	35	1,680

SPRINGS

Setting range (bar)	Pressure increase (bar/turn) Q = 4l/min	Standard setting (bar)
10 - 50*	7	30
20 - 100	12	75
10 - 180 standard	30	90
50 - 250	45	130
80 - 300	50	150

* For setting less than 70 Bar: Q = 12 l/min

ADJUSTEMENT

CODE/V	• Handknob
CODE/PP	• Arranged for sealing cap
CODE/PP	• Sealing cap